

TW Products® G100 hooks/fittings are:

- Forged Alloy Steel Quenched and Tempered
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification
- Each hook has a Product Identification Code for material traceability, along with the size and the name TW in raised letters (see illustration below)
- Suitable for use with Grade 100 and Grade 80 chain
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles
- Painted in TW's patented cyan blue
- Subject to an extended one-year after-sale warranty

TW1618-G100 OMEGALINK

B A D D D	ITEM CODE	WEIGHT (KG)	W.L.L.(T)	B.L(T)	A±0.5	B±2	E±1.5	M±2	L±2
	TW1618-06	0.12	1.4	5.6	8.5	32.5	20	44	55
	TW1618-08	0.27	2.5	10	10.5	42	24	60	73.5
	TW1618-10	0.44	4	16	12.5	48.5	31	70	90
	TW1618-13	0.89	6.7	26.8	16	60	38.5	90	109
	TW1618-16	1.69	10	40	19	75.5	51	112	141.5

- · Ultimate load is 4 times the Working Load Limit.
- · Regular marking information: 10 10 WLL 4 T CE TW + BATCH NUMBER.

