

TW Products® G100 hooks/fittings are:

- Forged Alloy Steel Quenched and Tempered
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification
- Each hook has a Product Identification Code for material traceability, along with the size and the name TW in raised letters (see illustration below)
- Suitable for use with Grade 100 and Grade 80 chain
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles
- Painted in chartreuse ® our registered trademark color
- Subject to an extended one-year after-sale warranty

	ITEM CODE	WEIGHT (KG)	W.L.L.(T)	B.L(T)	А	D±1	E±1	H±1	R±2	M±2	L±3
	TW1619-06	0.5	1.4	5.6	21	43	28	20	110	70	141
	TW1619-08	0.9	2.5	10	27	51	35.5	26	137	90	175
	TW1619-10	1.5	4	16	34.5	64.3	45	30	169	108	212.5
COTA	TW1619-13	2.7	6.7	26.8	40	80	53.5	40.5	209	138.5	270
	TW1619-16	5.7	10	40	50	104	62	50.5	254	170.5	331
	TW1619-20	7.9	16	64	60	120	76.5	62	277	192.5	369
M	TW1619-22	11.2	19	76	70	134	80	66	319.5	205	417

EYE SELF- LOCKING HOOK- TW1619

· Ultimate load is 4 times the Working Load Limit.