




TW Products® G100 hooks/ fittings are:

- Forged Alloy Steel - Quenched and Tempered
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification
- Each hook has a Product Identification Code for material traceability, along with the size and the name TW in raised letters (see illustration below)
- Suitable for use with Grade 100 and Grade 80 chain
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles
- Painted in chartreuse ® our registered trademark color
- Subject to an extended one-year after-sale warranty

SWIVEL SELF- LOCKING HOOK - TW1621

	ITEM CODE	WEIGHT (KG)	W.L.L.(T)	B.L(T)	B±1	C±1	D±0.5	E±1	H±1	M±2	L±3
	TW1621-06	0.6	1.4	5.6	32.5	23	11.5	28	20	70	184
	TW1621-08	1.1	2.5	10	36	28	13	35.5	26	90	229
	TW1621-10	2	4	16	42	35	15.5	45	30	108	269
	TW1621-13	4	6.7	26.8	50	40	17	53.5	40.5	138.5	330
	TW1621-16	6.8	10	40	61	56	21.5	62	50.5	170.5	413
	TW1621-20	12.5	16	64	72	62	26	76.5	62	192.5	463
	TW1621-22	17.1	19	76	97	94	33	80	66	205	572

- Ultimate load is 4 times the Working Load Limit.
- Regular marking information: 10 - 10 WLL 4 T CE TW + BATCH NUMBER.

