




# TW PRODUCTS

Rigging Hardware, Chain, Wire Rope & Synthetic Products

- Forged Alloy Steel - Quenched and Tempered
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification
- Each hook has a Product Identification Code for material traceability, along with the size and the name TW in raised letters (see illustration below)
- Suitable for use with Grade 100 chain
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles
- Painted in chartreuse® our registered trademark color
- Subject to an extended one-year after-sale warranty



## TW1642 - G100 Clevis Sling Hook

	WEIGHT (kg)	WLL (T)	B.L (T)	A	B	E	M	W	L'	L	Φ
	0.22	1.4	5.6	7.5±0.5	32±1.5	18±1	8±1	43.5±2	25.5±1.5	44.5±3	77.3±2
	0.34	2.5	10	9.5±0.5	36±1.5	24±1.5	11±1	54±2	33.5±1.5	53±3	93±3
	0.82	4	16	12.5±0.5	46±1.5	29.5±1.5	13.5±1.5	72±2	42±2	73±3	127±3
	1.75	6.7	26.8	15±1	59±1.5	37±1.5	15±1.5	96±2	53.5±2	92±4	164±4
	2.88	10	40	18.5±1	70±2	46±2	19±1.5	115±3	74±2.5	99±4	188±4
	4.84	16	64	24±1.5	85±2	52±2	25±2	145±3	87±2.5	123±5	223±5
	8.3	19	76	27±2	100±2.5	61±2.5	27±2	159±3	90±3	141±5	260±5
	13.72	26.5	106	30±2	110±2.5	70±2.5	34±2	190±4	110±3	187±5	320±5

Ultimate load is 4 times the Working Load Limit.