



TW PRODUCTS

Chain, Wire Rope & Rigging Hardware

STRAIGHT LINK COIL CHAIN NACM90



| Trade size | | Material diameter | | Working load (MAX) | | Proof test (MIN) | | Breaking force MIN | | Nominal inside length | | Nominal inside width | |
|------------|-----|-------------------|-------|--------------------|-----|------------------|------|--------------------|------|-----------------------|------|----------------------|------|
| MM | NO | MM | IN | KG | LBS | KN | LBS | KN | LBS | MM | IN | MM | IN |
| 3.0 | 4 | 3.0 | 0.120 | 93 | 205 | 1.82 | 410 | 3.64 | 820 | 28.1 | 1.11 | 5.32 | 0.21 |
| 3.4 | 3 | 3.4 | 0.135 | 116 | 255 | 2.27 | 510 | 4.53 | 1020 | 29.8 | 1.17 | 6.09 | 0.24 |
| 3.8 | 2 | 3.8 | 0.148 | 141 | 310 | 2.76 | 620 | 5.51 | 1240 | 29.9 | 1.18 | 6.59 | 0.26 |
| 4.1 | 1 | 4.1 | 0.162 | 168 | 370 | 3.29 | 740 | 6.58 | 1480 | 31.7 | 1.25 | 7.10 | 0.28 |
| 4.5 | 1/0 | 4.5 | 0.177 | 200 | 440 | 3.91 | 880 | 7.82 | 1760 | 31.7 | 1.25 | 7.86 | 0.31 |
| 4.9 | 2/0 | 4.9 | 0.192 | 236 | 520 | 4.63 | 1040 | 9.24 | 2080 | 31.9 | 1.26 | 8.62 | 0.34 |
| 5.3 | 3/0 | 5.3 | 0.207 | 274 | 605 | 5.38 | 1210 | 10.76 | 2420 | 32.9 | 1.30 | 9.13 | 0.36 |
| 5.5 | 4/0 | 5.5 | 0.218 | 304 | 670 | 5.96 | 1340 | 11.91 | 2680 | 35.2 | 1.39 | 9.64 | 0.38 |
| 6.4 | 5/0 | 6.4 | 0.250 | 399 | 880 | 7.83 | 1760 | 15.64 | 3520 | 38.5 | 1.52 | 11.20 | 0.44 |