




TW PRODUCTS

Chain, Wire Rope & Rigging Hardware

SCREW PIN ANCHOR SHACKLES



Screw Pin Anchor Shackles
Meet the performance requirements
of Federal Specification RR-C-271D
Type IVA, Grade A, Class 2

Bolt Type Anchor shackles
Meet the performance requirements
of Federal Specification RR-C-271D
Type IVA, Grade A, Class 3

Nominal Size (IN.)	W. L. L. (LBS)	Weight Each (LBS)	Dimensions(MM)											Tolerance +/-	
			A	B	C	D	E	F	G	H	L	M	P	C	A
3/16	660	0.07	9.65	6.35	22.4	4.85	15.2	14.2	24.9	37.3	4.06	28.4	4.85	1.50	1.50
1/4	1100	0.11	11.5	7.85	28.7	6.35	19.8	15.5	32.5	46.7	4.85	35.1	6.35	1.50	1.50
5/16	1650	0.20	13.5	9.65	31.0	7.85	21.3	19.1	37.3	53.0	5.60	42.2	7.85	3.30	1.50
3/8	2200	0.31	16.8	11.2	36.6	9.65	26.2	23.1	45.2	63.0	6.35	51.5	9.65	3.30	1.50
7/16	3300	0.37	19.1	12.7	42.9	11.2	29.5	26.9	51.5	74.0	7.85	60.5	11.2	3.30	1.50
1/2	4400	0.73	20.6	16.0	47.8	12.7	33.3	30.2	58.5	83.5	9.65	68.5	12.7	3.30	1.50
5/8	7150	1.36	26.9	19.1	60.5	16.0	42.9	38.1	74.5	106	11.2	85	17.5	6.35	1.50
3/4	10450	2.35	31.8	22.4	71.5	19.1	51.0	46.0	89.0	126	12.7	101	20.6	6.35	1.50
7/8	14300	3.61	36.6	25.4	84.0	22.4	58.0	53.0	102	148	12.7	114	24.6	6.35	1.50
1	18700	5.01	42.9	28.7	95.5	25.4	68.5	60.5	119	167	14.2	129	26.9	6.35	1.50
1-1/8	20900	7.39	46.0	31.8	108	29.5	74.0	68.5	131	190	16.0	142	31.8	6.35	1.50
1-1/4	26400	9.48	51.5	35.1	119	32.8	82.5	76.0	146	210	17.5	156	35.1	6.35	1.50
1-3/8	29700	13.51	57.0	38.1	133	26.1	92.0	84.0	162	233	19.1	174	38.1	6.35	3.30
1-1/2	37400	17.16	60.5	41.4	146	39.1	98.5	92.0	175	254	20.6	187	41.1	6.35	3.30
1-3/4	55000	27.7	73.0	51.0	178	46.7	127	106	225	313	25.4	231	57.0	6.35	3.30
2	77000	44.9	82.5	57.0	197	53	146	122	253	348	31.0	263	60.0	6.35	3.30
2-1/2	121000	85.6	105	70.0	267	69	184	145	327	453	35.1	330	79.5	6.35	6.35

Maximum Proof Load is 2 times the Working Load Limit. Minimum Ultimate Strength is 6 times the Working Load Limit.